Prohibition sticker "Smoking prohibited" Ø 430 mm

Article number	172803	**Sales unit quantity**	1 Piece
Colour	Red	**Sales unit EAN**	4005546983288
Packaging unit	piece	**Packing weight (gross)**	111.6 G
Base EAN	4005546983288	**Country of origin**	GB





Product description

- 'No Smoking' floor sticker (P002) for indoor prohibition and safety signage
- For floor markings, health and safety, fire safety and prohibition signs in production, logistics, warehousing and operational areas
- Self-adhesive version for application to smooth, surfaces with high load capacity that are free from grease and dust
- An abrasion-resistant and hard-wearing design for high-traffic areas
- Diameter 430 mm, material thickness 0.2 mm
- Compliant with ASR A1.3 and DIN EN ISO 7010
- Slip resistance (R Group) R9 in accordance with German workplace ordinance ASR A1.5/1,2 'Floors' per DIN 51130

Product features

Outer height (mm)	1
Outer Ø (mm)	430
Brand	DURABLE
Shape	Round
Safety symbol type	Prohibition sign
Symbol / Icon	Smoking Prohibited

DURABLE Hunke & Jochheim GmbH & Co. KG
Westfalenstraße 77 – 79 · 58636 Iserlohn · Germany
Phone +49 (0) 2371 662 0 · **Fax** +49 (0) 2371 662 221
Mail durable@durable.de | durable.de

The statements contained herein are for informational purposes only and are true and accurate to the best of our scientific and technical knowledge. This information does not constitute a guarantee or warranty, express or implied, nor does it establish a legally valid contractual relationship. It is the customer's responsibility to determine the suitability of this product for the customer's intended use. DURABLE does not assume any liability for the customer's use of this product or the information contained herein.

TÜVRheinland CERTIFIED
Management System
ISO 14001:2015
ISO 9001:2015
www.tuv.com
ID 0091005181

Prohibition sticker "Smoking prohibited" Ø 430 mm

Technical standard symbol reference	P002 according to ISO 7010
Mark language	Neutral
Self-adhesive type	Permanent
Adhesive strength	Normal
Abrasion resistance	Normal
Material thickness	0.4 mm
Special colour	Similar to RAL 3001 signal red
Colour	Red / white / black
Application area	Walking area, driving area
Technical standard	ASR A1.3, DIN EN ISO 7010, ASR A1.5/1,2 ''Floors''according to DIN 51130 Slip resistance (R group) R9

DURABLE Hunke & Jochheim GmbH & Co. KG
Westfalenstraße 77 – 79 · 58636 Iserlohn · Germany
Phone +49 (0) 2371 662 0 · **Fax** +49 (0) 2371 662 221
Mail durable@durable.de | durable.de

The statements contained herein are for informational purposes only and are true and accurate to the best of our scientific and technical knowledge. This information does not constitute a guarantee or warranty, express or implied, nor does it establish a legally valid contractual relationship. It is the customer's responsibility to determine the suitability of this product for the customer's intended use. DURABLE does not assume any liability for the customer's use of this product or the information contained herein.

TÜVRheinland CERTIFIED
Management System
ISO 14001:2015
ISO 9001:2015
www.tuv.com
ID 0091005181