Product data sheet

Mandatory sticker "Use safety vest" Ø 430 mm

Article number	173506	**Sales unit quantity**	1 Piece
Colour	Blue	**Sales unit EAN**	4005546983516
Packaging unit	piece	**Packing weight (gross)**	113.2 G
Base EAN	4005546983516	**Country of origin**	GB





Product description

- 'Wear a high-visibility vest' floor sticker (M015) for Indoor regulatory and safety signage
- For floor markings, health and safety signage and mandatory signage in production, logistics, warehousing and technical operational areas
- Self-adhesive version for application to smooth, surfaces with high load capacity that are free from grease and dust
- An abrasion-resistant and hard-wearing design for high-traffic areas
- Diameter 430 mm, material thickness 0.2 mm
- Compliant with ASR A1.3 and DIN EN ISO 7010
- Slip resistance (R Group) R9 in accordance with German workplace ordinance ASR A1.5/1,2 'Floors' per DIN 51130

Product features

Outer height (mm)	1
Outer Ø (mm)	430
Brand	DURABLE
Shape	Round
Safety symbol type	Command sign
Symbol / Icon	Use safety waistcoat
Technical standard symbol reference	M015 according to ISO 7010

DURABLE Hunke & Jochheim GmbH & Co. KG
Westfalenstraße 77 – 79 · 58636 Iserlohn · Germany
Phone +49 (0) 2371 662 0 · **Fax** +49 (0) 2371 662 221
Mail durable@durable.de | durable.de

The statements contained herein are for informational purposes only and are true and accurate to the best of our scientific and technical knowledge. This information does not constitute a guarantee or warranty, express or implied, nor does it establish a legally valid contractual relationship. It is the customer's responsibility to determine the suitability of this product for the customer's intended use. DURABLE does not assume any liability for the customer's use of this product or the information contained herein.

TÜVRheinland CERTIFIED
Management System
ISO 14001:2015
ISO 9001:2015
www.tuv.com ID 0091005181

Mandatory sticker "Use safety vest" Ø 430 mm

Mark language	Neutral
Self-adhesive type	Permanent
Adhesive strength	Normal
Abrasion resistance	Normal
Material thickness	0.4 mm
Special colour	Similar to RAL 5005 signal blue
Colour	Blue / white
Application area	Walking area, driving area
Technical standard	ASR A1.3, DIN EN ISO 7010, ASR A1.5/1,2 "Floors"according to DIN 51130 Slip resistance (R group) R9

DURABLE Hunke & Jochheim GmbH & Co. KG
Westfalenstraße 77 – 79 · 58636 Iserlohn · Germany
Phone +49 (0) 2371 662 0 · **Fax** +49 (0) 2371 662 221
Mail durable@durable.de | durable.de

The statements contained herein are for informational purposes only and are true and accurate to the best of our scientific and technical knowledge. This information does not constitute a guarantee or warranty, express or implied, nor does it establish a legally valid contractual relationship. It is the customer's responsibility to determine the suitability of this product for the customer's intended use. DURABLE does not assume any liability for the customer's use of this product or the information contained herein.

TÜVRheinland CERTIFIED
Management System
ISO 14001:2015
ISO 9001:2015
www.tuv.com
ID 0091005181